

Assignment 1

Create public class **ParkingSpace** which has:

- Private attribute *free* which indicates whether the parking space is free; it has the value true if the parking space is free, otherwise its value is false.
- Private attribute *registrationNumber* which represents the registration number of the vehicle parked at that space (type String).
- Set and get methods for these two attributes.

Create public class **ParkingLot** which has:

- Private attribute *parkingSpaces* which is an array of objects of the *ParkingSpace* class.
- Public constructor having the capacity of the parking lot (i.e., the total number of parking spaces) as its input parameter. If the value of this parameter is greater than zero, the *parkingSpaces* array should be initialized to that value. Otherwise (i.e., if the value of the input parameter is less than or equal to zero), the capacity of the parking lot should be set to 40 and an error message should be printed to the screen. In both cases all parking spaces (i.e., the elements of the *parkingSpaces* array) should be initialized and set to be free.
- Public method which checks if there is a free parking space; the method returns true if there is at least one free parking space, otherwise it returns false.
- Public method for 'parking' a vehicle. The input parameter of this method is the registration number of the vehicle to be parked. One should first check if there are still free spaces at the parking lot; if yes, the vehicle should be 'parked' at the first free space; if not, an appropriate message should be printed on the screen.
- Public method which checks if the vehicle with the given registration number is at the parking lot; the method returns true if the vehicle is found, otherwise it returns false; the registration number of the vehicle to be checked is passed to the method as its input parameter. *(students do on their own)*
- Public method for removing a vehicle from the parking lot. The input parameter of this method is the registration number of the vehicle to be removed. One should first check if there is a vehicle with the given registration number at the parking lot; if yes, the vehicle should be removed, so that the parking space becomes free again; if not, an appropriate message should be printed on the screen. Removing a vehicle assumes that the parking space occupied by that vehicle is set free and the data about vehicle's registration number are destroyed. *(students do on their own)*

Create the **TestParkingLot** class. In the main method of this class create an object of the class *ParkingLot* with the capacity of 20 parking spaces; park two vehicles with the following registration numbers: "BG 123-456" and "NS 234-56".

Assignment 2

Create public class **Motorcycle** which has:

- Private attribute *brand*
- Private attribute *model*
- Private attribute *enginePower*.
- Get and set attributes for these three attributes.

This class should also:

- Redefine the method *toString* inherited from the Object class; the method should return a string containing values of all the attributes.
- Redefine the *equals* method inherited from the Object class. Even though the signature of this method states that it has an input parameter of the type Object, we will assume that only objects of the class Motorcycle will be passed to it. This method should return true if values of all three attributes (*brand*, *model*, *enginePower*) of the two objects that are compared are equal; otherwise it returns false.

Create public class **MotorcycleRegistry** which has:

- Private attribute *motorcycles* which represents a list of objects of the *Motorcycle* class
- Public constructor which initializes the *motorcycles* attribute.
- Public method *isInRegistry* which receives an object of the class Motorcycle (as its input parameter) and checks if the same motorcycle is already in the registry.
- Public method *addToRegistry* which receives an object of the class Motorcycle (as its input parameter); the method should first check that the input parameter is not null and the registry does not already contain the same motorcycle; if both requirements are fulfilled the new motorcycle is added to the registry. (*students do on their own*)
- Public method *deleteFromRegistry* which receives an object of the class Motorcycle (as its input parameter) and deletes it from the registry; the deletion should take place only if the motorcycle to be deleted is in the registry. (*students do on their own*)
- Public method *print* which prints data about all motorcycles in the registry.

Create class **TestMotorcyclesRegistry**. In the main method of this class create an object of the *MotorcycleRegistry* class and three objects of the *Motorcycle* class using the following values for their attributes: "Honda" - "CB 750 F" - 748, "Kawasaki" - "ER 5" - 498 i "Honda" - "CB 750 F" - 748. First add the first two objects to the registry and then print the content of the registry. Subsequently check if the third motorcycle is in the registry and if yes, delete it from the registry. Finally, print again the content of the registry on the screen.